

TOM FORD



Enviralum™, entrances and window wall systems - the product of choice for architects and specifiers. Our products are designed to offer beauty, performance and value. All of our products are pre-fabricated and shop glazed to offer the highest quality and ease of installation.

Our systems are tested to Florida Building Code, High Velocity Hurricane Zone (HVHZ), the highest building standard in the nation. We offer variable glazing options within the product core designs to provide optimum flexibility in aesthetics and performance.

ENV-200 Narrow Stile Entrance Door

The ENV-200 narrow stile entrance doors is well proportioned with the vertical stiles measuring 2 1/8" the top rail measures 2 1/2" and the bottom rail 3 1/2". These have been made to the thinnest possible profile without sacrificing the performance which Enviralum™ is known for.

The ENV-200 provides one of the best aesthetics and performance in the industry with the most versatility offered. Its framing members are components of the ENV-4500 storefront system allowing them to work seamlessly together.

Product Features & Performance

- Maximum door leaf panel size 3'-6" x 8'-0" (nom.)
- Maximum design pressure +/-80 Impact
- Maximum design pressure +/-90 non-impact
- 1-point locking system by Regent & Adams Rite
- 3-point locking system by Regent & Adams Rite
- Panic exit devices Adams Rite & Regent
- Residential lever (multi-point locking mechanism by Regent)
- Offset pivots & butt hinges
- Continuous gear hinges by PEMKO & Select
- 1" diameter aluminum pull handles & push bars
- ADA compliant 4" saddle threshold
- ADA compliant bumper threshold with bulb gasket
- 1/4" Tempered monolithic glass (non-impact)
- 7/16" Heat Treated Laminated glass — Impact
- 1" Insulated Tempered glass units Non-impact
- 1" Insulated/Laminated glass units — Impact
- White powder coated finish - bronze & clear anodized
- Custom colors and high-performance coatings optional