



Enviralum™, entrances and window wall systems - the product of choice for architects and specifiers. Our products are designed to offer beauty, performance and value. All of our products are pre-fabricated and shop glazed to offer the highest quality and ease of installation.

Our systems are tested to Florida Building Code, High Velocity Hurricane Zone (HVHZ), the highest building standard in the nation. We offer variable glazing options within the product core designs to provide optimum flexibility in aesthetics and performance.

## Product Features & Performance

- Maximum door leaf size 4' x 10' (nom.)
- Maximum design pressure (LMI): +100 / -100
- Maximum design pressure (SMI): +110 / -144
- Water Rating: 9 PSF
- 3-Point locking mechanism by Adams Rite and Regent
- Panic exit devices by Adams Rite, Precision, Regent, Sargent and Von Duprin
- Residential Lever - 3-point locking mechanism by Interlock
- 4 1/2" x 4" ball bearing butt hinges in satin stainless steel by Regent, McKinney and Stanley
- Continuous gear hinges by PEMKO & Select
- 1" diameter aluminum pull handles and push bars
- ADA compliant threshold with bulb gasket
- 1/4" Tempered Monolithic - Non-impact
- 9/16" Heat Treated Laminated - Impact
- 1" Insulated Units - Non-Impact
- 1 5/16" Insulated / Laminated Units - Impact
- White powder coat - bronze & clear anodized (Kynar is optional)
- Custom colors and high-performance coatings optional

**NEW:** Level-E Glazing - provided for essential facilities

[www.enviralum.com](http://www.enviralum.com)

## ENV-350 Medium Stile Entrance Door

The ENV-350 medium stile entrance door is well proportioned with the stiles and top rail measuring 3 1/2" and the bottom rail 7". Both aesthetics and performance have been considered through multiple hardware options, high design pressures, in swing/out swing configurations and one of the largest panel dimensions in the market.

The ENV-350, with all of its features, stands alone on top of the entrance door industry. With the most locking mechanism options, largest sizes, highest design pressures, and the only in-swing panic with impact resistance.

The frame is 1 3/4" x 4 1/2" to match the ENV-450 so the two systems work hand-in-hand to complete most commercial or residential fenestration needs.